



Palletize Bags Affordable

The Bag Palletizer BP300 can palletize bags with a speed of up-to 300 units/hour and up-to 50kg.

For the basic version the pallet enters and exits the palletizing cell with a pallet jack.

Options such as pallet dispenser, roller conveyors for pallet outfeed and stretch wrapping machine are also available.

Bag Palletizing Application Examples

- Palletizing agricultural products (eg. potatoes, onions)
- Palletizing pellets
- Palletizing building materials

General Characteristics

COMPACT

Capable of being placed in limited spaces due to its small footprint.

PRODUCTIVITY

Capable of handling up-to 300 units per hour and up-to 50kg.

ADAPTABLE & CUSTOMIZABLE

The bag palletizer can adapt to any need. Based on its modular design, there are options such as bag flatteners, pallet dispensers, roller conveyors, stretch wrapping.

PALLET STABILITY

Pallet stability is guaranteed by layer interlocking, centering over the pallet.

SIMPLE USE

Its very easy to use. All functions are controlled from a touch screen with simple and intuitive menu.

FLEXIBLE

Can be programmed by the operator to build various layer patterns. Changing from one layer pattern to another is instant.

ACCURATE

Linear guide system for lifting and horizontal movements.

SMOOTH MOTION

Every gearmotor is controlled by an inverter providing smooth motion and fast acceleration / deceleration.

SAFE

Guarded by category 3 emergency circuit. Activated by category 4 safe emergency buttons, safety fence doors and muting light curtains.

RELIABLE

High quality manufacturing, use of standard and proven equipment maximizes reliability.

MINIMUM MAINTENANCE

Designed for minimum maintenance with components that can be easily accessed and with reduced need for support.

All aforementioned information are non-binding and are given without guarantee.

Productivity data and dimensioning for specific applications, can only be provided through an inquiry.

P12601.v1.0 KINEMATIK © 2012